







Tidal Compensator

Tidal Compensators are designed to help floating barriers self-adjust with changing water tides. The Tidal Compensator attaches on one end of the barrier and on the other end to a structure such as a dock. As the water level rises or recedes, the side floats self-adjust and the connector moves up and down an I-beam.



Tow Bridle

The Tow Bridle is one of many floating boom accessories designed to help with the installation and deployment of a floating boom. Equipped to help safely tow the curtain out into position, these bridles feature a small flotation device and two attachment points to help distribute weight evenly across



Anchoring Kits

Anchoring and Anchor Kits are one of the most important accessories for sites dealing with moving currents, waves, tides or other site factors. Having the right anchor pattern, installation design and anchors can significantly influence, reduce and redistribute loads placed on your barrier.



Buoys

Buoys, light buoys, and navigational aids are used to demarcate turbidity curtains while dredging, marking oil containment boom during oil spill recovery or simply on a debris barrier where marine traffic is present Buoys are also used as part of an anchoring system to help anchor the barrier without placing additional strain on the bottom of the curtain.



Marker Lights

Marker lights are a great way to increase visibility of a barrier in any given location. Lights include a buoy, light, and pole that allows the light to float in the water next to the boom.



Reefing Lines

Reefing lines are primarily designed for turbidity curtains and allow customers to adjust the depth of the barrier depending on tides and contours. Adjusting lines are ideal for areas with varying water depths. Reefing lines must be installed during the initial construction phase.



Ground Anchor Kit

Kit Part	Description
Anchor	Ground Anchor Style
Webbing	Sized to suit
Shackle	5/16"
Buoy	15" Orange Buoy
Installation Driver and Rod	Sold Separately - Not Included

Marine Anchor Kit

Kit Part	Description
Anchor	Ground Anchor Style
Rope	Sized to suit
Chain	5/16"
Buoy	15" Orange Buoy
Painter Liner	Sold Separately - Not Included
Hold Power	22lb/1600 , 40lb/2000 , 65lb/3000

Reefing Lines

Power Source

For curtain greater than 10' depth, reefing lines are recommended. For ease of deployment, removal, or for variegated bottom depths

Marine Marker Lights

Power Source	Description
D Cell Battery	Approximately 3 Weeks Per Set
Solar Powered	Rechargeable

Tidal Compensator

Туре	Grip
Standard (Calm Water)	Nylon Rollers (2 Per Section)
Heavy Duty (Moving Water)	Nylon Rollers (4 Per Section)

Tow Bridles

Style	Туре
12" - 48"	Selected to Match Barrier Type and Depth