

Aluminum Angle Berm OXO with Drive-Thru Ends



The OX Aluminum Angle Containment Berm with Drive-Thru Ends is the perfect choice for any location requiring the containment or storage of hazardous liquids discharge from equipment or vehicles. Built from a range of high-resistance fabrics and components, these berms are well equipped to handle UV exposure, outdoor use, extended containment, and short term contact with hazardous materials.



Aluminum Angle Berm

with Drive-Thru Ends

The OX Aluminum Angle Berm with Drive-Thru Ends is the perfect containment option for large objects or multiple small ones. These berms provide secondary containment for vehicles, equipment, frac tanks, valves, storage tanks, 55-gallon drums, paint drums, and chemical containers.

Aluminum angle brackets form rigid sides around your stored product while the ends are constructed of foam walls that allow vehicles or other equipment to drive onto the berm. Walls will typically feature a height of one foot to successfully contain materials in the event of a spill.

Applications

- Tank Containment
- Vehicle/Equipment Containment
- Fuel Tank Storage
- Frac Tank Spill Containment
- Valve and Leak Control
- Tote Spill Containment
- Spill Response
- Machinery or Fueling Stations

Advantages

- Easy to Set Up
- Folds Up for Storage & Transport
- Easy Drive-In/Drive-Out Options
- Cost-Effective Containment
- Effectively Contains Spilled Liquids
- Reliable Angle Exterior

Containment Berm Fabrics and Compatibility

Below you will find standard liner options for all of our containment berms. Additional liner materials and weights are available upon request.

Liner Material:

- 22 oz. PVC (yellow)
- 40 oz. PVC (black)
- 40 mil LLDPE (black)
- 30 oz. Elvaloy
- 32 oz. Polyurethane







Equipped to handle:

- Fuels (diesel fuel, gas, and more)
- Hydrocarbons/Oil
- · Chemicals
- Water (including frac water, chemical based water and more)
- Depending on your chemicals and liquid storage requirements, we may require customers to provide us with an MSDS (Material Safety Data Sheet) to help confirm compatibility with the chemicals you will be storing in the berm.

Aluminum Angle Berm

with Drive-Thru Ends

SPECIFICATIONS

Material Options

22 oz PVC	
36 mil PVC	
40 mil LLDPE	
30 oz. XR-5	
32 oz Polyurethane	

ACCESSORIES

- Berm Runners
- Storage Crates
- Ground Mats,
- Wear Pads
- Repair Kits
- Replacement Brackets

Dimensions	Capacity
6' (I.8 m) x 6' (I.8 m) x I' (0.305 m)	269 gal. (1,018 L)
8' (2.4 m) × 8' (2.4 m) × 1' (0.305 m)	479 gal. (1,813 L)
10' (3.05 m) x 10' (3.05 m) x 1' (0.305 m)	748 gal. (2,831 L)
10' (3.05 m) × 20' (6.10 m) × 1' (0.305 m)	1,496 gal. (5,663 L)
10' (3.0 m) × 50' (15.20 m) × 1' (0.305 m)	3,740 gal. (14,157 L)
12' (3.66 m) x 12' (3.70 m) x 1' (0.305 m)	1,077 gal. (4,077 L)
12' (3.66 m) x 20' (6.10 m) x 1' (0.305 m)	1,496 gal. (5,663 L)
12' (3.66 m) x 26' (7.90 m) x 1' (0.305 m)	2,334 gal. (8,835 L)
12' (3.66 m) × 30' (9.10m) × 1' (0.305 m)	2,693 gal. (10,194 L)
12' (3.66 m) x 36' (10.9 m) x 1' (0.305 m)	3,232 gal. (12,234 L)
12' (3.66 m) x 50' (15.2 m) x 1' (0.305 m)	4,488 gal. (16,989 L)
14' (4.27 m) x 54' (16.2m) x 1' (0.305 m)	5,610 gal. (21,236 L)
15' (4.57 m) x 15' (4.57 m) x 1' (0.305 m)	1,683 gal. (6371 L)
15' (4.57 m) x 5 0' (15.2 m) x 1' (0.305 m)	5,610 gal. (21,236 L)
15' (4.6m) x 66' (20.1 m) x 1' (0.305 m)	7,406 gal. (28,035 L)
16' (4.9 m) × 40' (12.20m) × 1' (0.305 m)	4,788 gal. (18,125 L)
16' (4.9 m) x 50' (15.20 m) x 1' (0.305 m)	7,481 gal. (28,319 L)

For more complete information on GEI Works products and solutions, visit us on the Web at www.geiworks.com.

Toll Free: I-888-703-9889 | Phone: (I+) 772-646-0597 | info@geiworks.com

© 2015 GEI Works All rights reserved GEI Works terms and conditions apply.

All photos are representatives only. Actual product may differ than featured.

Materials and specifications are subject to change without notice. Featured products in photos may include additional equipment or accessories. See your GEI Works Dealer for available options.

GEI Works, Mars, Taurus, Triton, Kraken, Orion, Vulcan and geiworks.com, their respective logos, product identity used herein, are trademarks of GEI Works and may not be used without permission.

